



GMI Composites, Inc. 1355 W.Sherman Blvd. Muskegon, MI 49441

800-330-4045 sales@gmicomposites.com

www.gmicomposites.com

Mtl Dsg	COL	Min Thk mm	UL94 Flame Class	Elec	RTI Mech with Imp	RTI Mech w/o Imp	H W I	H A I	H V T R	D 4 9 5	C T I
LA-14	NC	1.47		105	130	130					
		3.18		105	130	130					0
LA-XX	NC	1.47		105	130	130					
		3.18		105	130	130					0
LA-30	NC	1.47		105	130	130					
		3.18		105	130	130					0
GM 1010	ALL	1.52	94V-O	130	130	130	1	0			
		3.18	94V-O	130	130	130	0	0	0	4	0
		6.35	94V-O	130	130	130	0	0			
GM10YY		1.52		130	130	130		0			
		1.65	94V-O	130	130	130					
		3.18	94V-O	130	130	130	0	0	0	4	0
		6.35	94V-O	130	130	130	0	0			
GM 1020		1.52		130	130	130		0			
		1.65	94V-O	130	130	130					
		3.14	94V-O	130	130	130	0	0	0	4	0
		6.35	94V-O	130	130	130	0	0			
GM 10ZZ		1.78	94V-O	130	130	130		0			
		3.18	94V-O	130	130	130	0	0	0	4	0
		6.35	94V-O	130	130	130	0	0			
GM 1028		1.78	94V-O	130	130	130		0			
		3.18	94V-O	130	130	130	0	0	0	4	0
		6.35	94V-O	130	130	130	0	0			

Where XX represents glass contents from 15 to 29 percent.

Where YY represents glass contents from 15 to 29 percent.

Where ZZ represents glass contents from 15 to 29 percent.